



PennWhite

Econolub

water based thixotropic lubricant

technical data sheet

lubricants

Econolub is a water based thixotropic lubricant which will reduce friction during installation of telecommunication and fibre optic cable and sub-duct underground. It is based on a blend of silicone polymers and has been developed as a low cost cable lubricant.

TYPICAL PROPERTIES

Appearance:	White Thixotropic Pourable Gel.
Specific Gravity:	1.0
pH:	6-8

APPLICATION

Econolub can be used for both pulling and blowing cable installation. It can be poured directly onto cable or it can be applied inside the duct wall.

SPILLAGE

Econolub can be cleaned up with detergent and large amounts of water.

PACKAGING

Available in 20 litre pails, 200kg drums.

SHELF LIFE

12 Months from date of manufacture, protect from frost at all times.

(OPA2/F2)

TDS: 055

Issue: 04

Revised: 04/03/2014

Page 1 of 1

For additional technical or safety advice call us on 01606 734820 or email info@pennwhite.co.uk

PennWhite Ltd
Aston Way
Midpoint 18 Business Park
Middlewich, CW10 0HS



Telephone: +44 (0)1606 734820
Fax: +44 (0)1606 837867
Email: info@pennwhite.co.uk
Website: www.pennwhite.co.uk