



Foamdoctor G2960

foam control agent

PennWhite

technical data sheet

foam control agents - general grade

Foamdoctor G2960 is a powerful foam control agent based on an aqueous emulsion of vegetable oil, polyethers and non-ionic surfactants.

Foamdoctor G2960 is a highly cost effective product with excellent compatibility. It has a very fast action and a good control of foam even at low levels.

TYPICAL PROPERTIES

Appearance:	White emulsion
Viscosity:	500 – 1000cP
Solids:	25.0 – 27.0%
Dispersion:	Disperses in water

APPLICATION

Foamdoctor G2960 should be agitated before use and can be pre diluted in water for ease of application. Suggested dosage for typical applications:

Application	Area	Dosage
Water based coatings	Matt/silk paints, clear wood coatings and wood stains	0.1 – 0.4%
Building products	Cement admixtures and polymer reinforced concrete	0.2 – 0.5%
Adhesives	Water based/PVA adhesives	0.2 – 0.3%
Effluent	Starch and proteinaceous waste	100 – 200ppm
Fermentation	Production and effluent	50 – 300ppm
Water treatment	Boiler waters and cooling waters	50 – 500ppm
	Desalination (technical)	5 – 50ppm
	Glycol scrubbers	500 – 2000ppm

PACKAGING

Foamdoctor G2960 is available in 200kg drums.

SHELF LIFE AND STORAGE CONDITIONS

Keep container tightly closed. Store in a cool dry place between 5°C and 35°C. Protect from frost. Agitate well before use. Shelf life: 12 months in unopened containers.

(OPA2/F2)

TDS: 105

Issue: 05

Revised: 06/03/2014

Page 1 of 1

For additional technical or safety advice call us on 01606 734820 or email info@pennwhite.co.uk

PennWhite Ltd

Aston Way

Midpoint 18 Business Park

Middlewich, CW10 0HS

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: info@pennwhite.co.uk

Website: www.pennwhite.co.uk

